

Océ Transparent Plus Paper, 112 g/m²

Océ Transparent Plus Paper, 112 g/m² is a special coated transparent paper for inkjet. It is suitable for colour overlays and as an economic alternative for polyester film and Diazo reproduction.

Product description

Lightly coated transparent paper suitable for monochrome and colour line drawings

Physical properties

Weight	110 ± 3 g/m ²	ISO 536
Calliper	89 ± 3 microns	ISO 534
Opacity	> 33 %	Elrepho 3000 D65 10XLAV
Whiteness	64 ± 3 CIE	Elrepho 3000 D65 10XLAV
Roughness Bendtsen		ISO 8791
- frontside	240 ± 30 ml/min	
- backside	230 ± 30 ml/min	
Stiffness		ISO 2493 (15°; 10mm)
- machine direction	115 ± 15 mN	
- cross direction	65 ± 10 mN	

Features

Good dot gain control, resulting in fine line sharpness
 Suitable medium for monochrome and colour line drawings and low end GIS

Main applications Monochrome and colour CAD and low end GIS drawings

Océ Imaging Supplies
 Product Info

IJM141

Wide-format CAD
 Version 5

Océ Transparent Plus Paper, 112 g/m²

Océ Imaging
Supplies
Product Info

IJM141

Wide-format CAD

Version 1

Processing information Side to be printed is the outer side of the roll
Best results between 15° - 25°C and 30-70 %RH (especially higher humidity will increase drying time, low humidity may cause curl)
Correct maintenance of cartridges or printheads will result in optimal print quality. Please check your printer documentation for the recommended maintenance activities.

Outdoor suitability This material is not suitable for outdoor use

Storage conditions Temperature 10° - 30° C
Relative Humidity 20-80 %
Repack opened rolls when not in use
Allow material to adapt to room conditions 24 hours before printing

Health, safety & environment No Material Safety Data Sheet required
Waste can be handled as paper waste



Océ Transparent Plus Paper, 112 g/m²

Océ Imaging
Supplies
Product Info

IJM141

Wide-format CAD

Version 1

Performance on major CAD inkjet printers

	Type	Engineering (CAD)	Architecture (AEC)	Geographic Information Systems (GIS)	3D CAD	Posters & Presentations	Photo
Océ	TCS400	4	4	3	1	1	1
	5150 / 5250	4	4	3	1	1	1
	5200	4	4	3	1	1	1
	5120	4	4	3	1	1	1
	5100C	4	4	3	1	1	1
HP	5500 / 5500ps *	4	4	3	1	1	1
	5000 / 5000ps *	4	4	3	1	1	1
	3000cp / 3500cp / 3800cp *	4	4	3	1	1	1
	2000cp / 2500cp / 2800cp *	4	4	3	1	1	1
	1050C / 1055cm / 1050c plus / 1055cm plus	4	4	3	1	1	1
	500 / 500ps / 800 / 800ps	4	4	3	1	1	1
	750c / 750c plus / 755cm	4	4	3	1	1	1
Encad	Novajet 800 series	4	4	2/3	1	1	1
	Novajet 700 / 750	4	4	2/3	1	1	1
	Novajet 500	4	4	2/3	1	1	1
	Cadjet 3D	4	4	3	1	1	1
	Cadjet T-200	4	4	3	1	1	1
Canon	BJW-9000						
	BJW-3000 / BJW-3050	4	4	3	1	1	1
Calcomp	TechJET 5500 series	4	4	3	1	1	1
	TechJET 5300 series	4	4	3	1	1	1
	TechJET 720C	4	4	3	1	1	1
	TechJET 720	4	4	3	1	1	1
Selex	S 900D / S 900E	4	4	3	1	1	1
	SR 700 / SR 850D / SR 850E	4	4	3	1	1	1
	SR 700E / SR 700D / SR 710D/E	4	4	3	1	1	1

4: Excellent, 3: Good, 2: Fair, 1: Not recommended

Print quality mode: Normal

* : Only with dye ink

If your printer is not listed, please contact your local Océ supplies organisation

Océ-Technologies B.V.



P.O. box 101
5900 MA Venlo, the Netherlands
+31 (0) 77 3592222
www.oce.com

Page 3 of 3

Printing for
Professionals

© November 2007 Océ-Technologies B.V. Illustrations and specifications do not necessarily apply to the standard version of machines in all local markets. Technical specifications subject to change without prior notice. All products mentioned in this brochure are claimed as trademarks or registered trademarks of their respective companies.